

# ALKO Heavy Duty Axle



12,000 Lbs. Capacity with 120 Spindle



Standard Specifications			
Track*	74.00"	70.00"	66.00"
Hub Face	73.50"	69.50"	65.50"
Spring Center	46.00"	42.00"	38.00"
Over All	95.25"	91.25"	87.25"
Leaf Spring	Six Leaf Slipper at 6250 pounds		
U-Bolt	5/8" - 11 UNC x 10 1/2" (#5913)		
Tie Plate	(#7708)		
U-Bolt Nut	5/8" - 11 UNC - 2B (#6713)		

\*Track assumes a wheel disc thickness of 1/4"

Features
<ul style="list-style-type: none"><li>• Axle is constructed of 5 1/8" x 5/16" wall tube</li><li>• Spindle is fully machined from cold forged material, press fit and welded for strength and alignment.</li><li>• The two piece hub and drum assembly has a replaceable steel armature for use with electric brakes.</li><li>• AL-KO oil caps are molded from high strength polycarbonate to minimize breakage and leakage.</li><li>• Timken bearings and races are lubricated with SAE 90 weight oil assuring long bearing life.</li><li>• Available with 12 1/4" x 3 1/2" self adjusting, hydraulic or electric brakes.</li><li>• AP kits available for 48 1/4" or 42 1/4" axle spacing.</li><li>• Rubber bushed equalizer prevents front axle hopping under braking conditions.</li></ul>

## ALKO KOBER CORPORATION

21611 Protecta Dr.  
Elkhart, IN 46516  
219-294-6651  
219-294-7267 Fax

301 N. Kennedy  
Shawnee, OK 74801  
405-273-9315  
405-273-1054 Fax

315 Road 911  
Baldwyn, MS 38824  
601-365-5566  
601-365-9222 Fax